

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SYNTOPRIMER RAL9016c

Product code : 000000000000011005
11005

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Primers
stance/Mixture

1.3 Details of the supplier of the safety data sheet

Karl Bubenhofer AG
Hirschenstrasse 26
CH-9201 Gossau SG
Telefon: +41 (0)71/387 41 41, Telefax: +41 (0)71/387 41 51
Auskunftgebender Bereich (Bürozeiten):
Verantwortliche Chemikalien-/Produktesicherheit, Dr. Christina Ott
Telefon: +41 (0)71/387 41 35, Telefax: +41 (0)71/387 43 04
Email: regulatory@kabe-farben.ch

- Vertrieb Deutschland
KABE Pulverlack Deutschland GmbH Sofienstrasse 36 D-76676 Graben-Neudorf Telefon: +49
(0)7255 99-161, Telefax: +49(0)7255
99-163 (Bürozeiten)
- Vertrieb Österreich:
KABE-Farben GmbH Langegasse 31 A-6850 Dornbirn Telefon (Bürozeiten): +43 (0)5572-21568, Tele-
fax: +43 (0)5572-2094
- Vertrieb Polen:
Farby KABE Polska Sp. z o.o. ul. Slaska 88, 40-742 Katowice tel. +48 32 204 64 60, fax +48 32 204
64 66, (Bürozeiten),
proszkowie@farbykabe.pl

1.4 Emergency telephone number

Switzerland: Poisoning emergencies: Tox Info Suisse, telephone: +41 (0)44/251 66 66 or 145 (only within Switzerland)
Germany: Poison Control Center Berlin: +49(0)30-19240
Austria: Poison Control Center AKA Vienna: +43(0)1/4064343
Poland: National Poison Information Center and Clinical Department of Toxicology: +48(42)6579900

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3

H226: Flammable liquid and vapour.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms

:



Signal word

:

Warning

Hazard statements

:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist or vapours.
P264	Wash skin thoroughly after handling.
P273	Avoid release to the environment.

Response:

P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.

Hazardous components which must be listed on the label:

reaction mass of ethylbenzene and xylene
64742-82-1

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version 1.3 Revision Date: 13.01.2025 SDS Number: 100000000553 Date of last issue: 11.12.2023
Date of first issue: 13.01.2023

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Paint

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304	>= 20 - < 30
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 2,5 - < 10
64742-82-1		Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 2,5 - < 10
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	1174522-20-3 919-857-5	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	>= 1 - < 10
1-methoxy-2-propanol	107-98-2 203-539-1	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 10

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version 1.3 Revision Date: 13.01.2025 SDS Number: 100000000553 Date of last issue: 11.12.2023
Date of first issue: 13.01.2023

	603-064-00-3	(Central nervous system)	
zinc oxide	1314-13-2 215-222-5 030-013-00-7	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1	>= 0,1 - < 0,25
Substances with a workplace exposure limit :			
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6 238-877-9		>= 10 - < 20
calcium carbonate	471-34-1 207-439-9		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6	TWA (Respirable dust)	1 mg/m ³	GB EH40
		TWA (Respirable dust)	0,1 mg/m ³	2004/37/EC
Further information: Carcinogens or mutagens				
calcium carbonate	471-34-1	TWA (inhalable dust)	10 mg/m ³	GB EH40
		TWA (Respirable dust)	4 mg/m ³	GB EH40
1-methoxy-2-propanol	107-98-2	STEL	150 ppm 560 mg/m ³	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		TWA	100 ppm 375 mg/m ³	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL	150 ppm 568 mg/m ³	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		TWA	100 ppm 375 mg/m ³	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				

Predicted No Effect Concentration (PNEC)

Substance name	Environmental Compartment	Value
----------------	---------------------------	-------

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

Remarks : The choice of an appropriate glove does not only depend on

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

its material but also on other quality features and is different from one producer to the other. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Skin should be washed after contact. Use a high fat protective cream after cleaning skin.

- Skin and body protection : Workers should wear antistatic footwear.
Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Protective measures : In case of insufficient ventilation, wear suitable respiratory equipment.
Ensure staff are informed of and trained on the nature of exposure and basic actions to minimise exposure.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : pigmented
- Odour : slight
- pH : substance/mixture is non-soluble (in water)
- Flash point : 24,0 °C
Method: Measured value
- Density : 1,9843 g/cm³ (20 °C)
Method: Calculated value
- Solubility(ies)
Water solubility : insoluble
- Viscosity
Viscosity, kinematic : > 20,5 mm²/s (40 °C)

9.2 Other information

No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Not applicable

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified due to lack of data.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 (Rat): 5.251 mg/kg

Acute inhalation toxicity : LC50: 6700 ppm
Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is moderately toxic after short term inhalation.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg

Assessment: The component/mixture is moderately toxic after single contact with skin.

trizinc bis(orthophosphate):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

64742-82-1:

Acute oral toxicity : LD50 (Rat): > 15.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): 3.400 mg/kg

1-methoxy-2-propanol:

Acute oral toxicity : LD50 (Rat): 4.016 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25,8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

zinc oxide:

Acute oral toxicity : LD50 (Rat): > 15.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5,7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402

calcium carbonate:

Acute oral toxicity : LD50 (Rat): 6.450 mg/kg

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

Skin corrosion/irritation

Causes skin irritation.

Components:

reaction mass of ethylbenzene and xylene:

Result : Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

reaction mass of ethylbenzene and xylene:

Result : Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

Components:

reaction mass of ethylbenzene and xylene:

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

64742-82-1:

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

reaction mass of ethylbenzene and xylene:

Exposure routes	: Inhalation
Target Organs	: hearing organs
Assessment	: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

64742-82-1:

Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Aspiration toxicity

Not classified due to lack of data.

Components:

reaction mass of ethylbenzene and xylene:

May be fatal if swallowed and enters airways.

64742-82-1:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

trizinc bis(orthophosphate):

Toxicity to fish : LC50 (Fish): > 0,14 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 2,44 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): 0,8 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

64742-82-1:

Toxicity to fish : LC50 (Fish): > 10 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): > 10,0 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): > 4,6 mg/l
Exposure time: 72 h

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

1-methoxy-2-propanol:

Toxicity to fish : LC50 (Fish): 6.812 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 21.100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): > 100 mg/l
Exposure time: 72 h

zinc oxide:

Toxicity to fish : LC50 (Fish): 1,10 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 0,413 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): 0,136 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

Talc (Mg3H2(SiO3)4):

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

Toxicity to fish : LC50 (Fish): > 10.000 mg/l
Exposure time: 96 h

calcium carbonate:

Toxicity to fish : LC50 (Fish): 2.000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): > 1.000 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (algae): > 200 mg/l
plants Exposure time: 72 h

12.2 Persistence and degradability

Components:

trizinc bis(orthophosphate):

Biodegradability :
Result: Not biodegradable

64742-82-1:

Biodegradability :
Result: Readily biodegradable.

1-methoxy-2-propanol:

Biodegradability :
Result: Readily biodegradable.

zinc oxide:

Biodegradability :
Result: Readily biodegradable.

calcium carbonate:

Biodegradability :
Result: Not readily biodegradable.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Dispose of in accordance with local regulations.
Refer to manufacturer/ supplier/ for information on disposal/ recovery/ recycling.
The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
Packaging that is not properly emptied must be disposed of as the unused product.

SECTION 14: Transport information

14.1 UN number

ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
IATA	: UN 1263

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

14.2 UN proper shipping name

ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT (trizinc bis(orthophosphate), naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha)
IATA	:	Paint

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADR	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: (D/E)
RID	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
IMDG	
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
IATA (Cargo)	
Packing instruction (cargo aircraft)	: 366
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids
IATA (Passenger)	
Packing instruction (passenger aircraft)	: 355
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids

14.5 Environmental hazards

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Conditions of restriction for the following entries should be considered: Number on list 3: reaction mass of ethylbenzene and xylene, 64742-82-1, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, 1-methoxy-2-propanol, 2-Pentanone, oxime, xylene, 1,2,4-trimethylbenzene, xylene, 64742-48-9, ethylbenzene, 1174522-09-8, 2-methylpropan-1-ol, n-octane, 2-methoxypropanol, 2-methylpentane-2,4-diol Number on list 3 Number on list 30: 2-methoxypropanol
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	: Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	: Not applicable
Regulation (EC) on substances that deplete the ozone layer	: Not applicable
UK REACH List of substances subject to authorisation	: Not applicable

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

(Annex XIV)

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : reaction mass of ethylbenzene and xylene
64742-82-1
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
1-methoxy-2-propanol
trizinc bis(orthophosphate)
Talc (Mg₃H₂(SiO₃)₄)
calcium carbonate

P5c

E1

Control of Major Accident Hazards Regulations 2015 (COMAH)	P5c	FLAMMABLE LIQUIDS
	E2	ENVIRONMENTAL HAZARDS
	E2	

Volatile organic compounds : 33,8 %

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

TCSI	: Not in compliance with the inventory
TSCA	: Product contains substance(s) not listed on TSCA inventory.
AIIC	: Not in compliance with the inventory
DSL	: This product contains the following components that are not on the Canadian DSL nor NDSL. reaction mass of ethylbenzene and xylene Alkyd resins 13463-67-7 64742-82-1 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Polyesterharz

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

Quaternary ammonium compounds, benzyl(hydrogenated
tallow alkyl)dimethyl, stearates, salts with bentonite

64742-48-9
1174522-09-8

2-Pentanone, oxime
neodecanoic acid, zirconium salt

ENCS	:	Not in compliance with the inventory
ISHL	:	Not in compliance with the inventory
KECI	:	Not in compliance with the inventory
PICCS	:	Not in compliance with the inventory
IECSC	:	Not in compliance with the inventory
NZIoC	:	Not in compliance with the inventory
TECI	:	Not in compliance with the inventory

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H372	:	Causes damage to organs through prolonged or repeated exposure.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2004/37/EC / TWA	:	Long term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3 H226

Classification procedure:

Based on product data or assessment

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



KARL BUBENHOFER AG

SYNTOPRIMER RAL9016c

Version	Revision Date:	SDS Number:	Date of last issue: 11.12.2023
1.3	13.01.2025	100000000553	Date of first issue: 13.01.2023

Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / 6N